

AES-HM76Z1FL

Fanless and Ultra Slim Intel HM76 Embedded System



Features

- Fanless and ultra slim design
- Support Intel Ivy Bridge CPU with HM76 chipset
- 2 x DDR3 SO-DIMM, up to 16GB
- Support SATA III and CF storage
- HDMI/VGA/USB/Audio/GPIO output interface
- Serial ports by RS-232 and RS-422/485
- 2 x GbE, 1 x SIM, and 1 x MiniPCle(for 3G/WiFi)



Specification

System

CPU	Intel Core i7 3517UE 1.7GHz Intel Core i3 3217UE 1.6GHz Intel Celeron Processor 1047UE 1.4GHz Intel Celeron Processor 927UE 1.5GHz
------------	---

Chipset	Intel HM76
----------------	------------

Memory	2 x 204-pin SO-DIMM sockets support 1333/1600MHz DDR3 up to 16GB
---------------	---

BIOS	AMI UEFI BIOS
-------------	---------------

Hardware Monitoring	CPU voltage and temperature
----------------------------	-----------------------------

WatchDog Timer	Software programmable 1~255 sec.
-----------------------	----------------------------------

Video

Graphic Controller	Integrated within HM76
---------------------------	------------------------

Video Interface	<ul style="list-style-type: none"> ● 2 x HDMI (HDMI Type A connector) ● 1 x VGA (Combo connector)
------------------------	---

Ethernet

Ethernet	<ul style="list-style-type: none"> ● 2 x GbE (RJ45 with LED) ● Realtek RTL8111F
-----------------	---

Storage

SATA	1 x SATA III port with SATA power connector
-------------	---

CF	1 x Compact Flash Type II socket
-----------	----------------------------------

I/O

Expansion	1 x MiniPCle socket(For 3.5G/WiFi)
------------------	------------------------------------

SIM	1 x SIM slot (SIM card changeable without opening case)
------------	---

USB	<ul style="list-style-type: none"> ● 3 x USB 3.0 (USB 3.0 Type A connector) ● 2 x USB 2.0 (1 for MiniPCle / 1 for Combo connector)
------------	--

Serial Port	<ul style="list-style-type: none"> ● 2 x RS-232 (DB9 connector) ● 2 x RS-422/485 (DB15 connector, shared with GPIO)
--------------------	---

GPIO	<ul style="list-style-type: none"> ● 8 x GPI (DB15 connector, shared with RS-422/485) ● 8 x GPO (DB15 connector, shared with RS-422/485)
-------------	--

Audio	<ul style="list-style-type: none"> ● 1 x Line-Out (Combo connector) ● Realtek ALC662
--------------	--

Power Requirement	
--------------------------	--

Power Supply	60W Power Adaptor (DC Jack)
---------------------	-----------------------------

Power Requirement	12VDC Single Voltage Input
--------------------------	----------------------------

Software

OS Support	Windows 7(32/64bit), Windows 7 Embedded(32bit), Fedora 17(32/64bit), uBuntu 12.10(32/64bit)
-------------------	---

Mechanical & Environment

Thermal Design	Fanless (Heatsink)
-----------------------	--------------------

Dimension	272 mm x 183 mm x 20 mm
------------------	-------------------------

Operating Temp.	0 ~ 45°C (32 ~ 113°F)
------------------------	-----------------------

Storage Temp.	-20 ~ 80°C (-4 ~ 176°F)
----------------------	-------------------------

Relative Humidity	0 ~ 90%, non-condensing
--------------------------	-------------------------

Safety	CE, FCC class A
---------------	-----------------

Packing List

- 1 x AES-HM76Z1FL
- 1 x Quick Manual
- 1 x Utility CD
- 1 x Combo Cable
- 2 x GPIO Cable
- 1 x 60W Power Adapter
- 1 x Power Cord (Option for USA or Europe or Japan or UK)

Option

WiFi Module Kit	WiFi module, RF cable, Antenna
------------------------	--------------------------------

3.5G Module Kit	3.5G module, RF cable, Antenna
------------------------	--------------------------------

Ordering Information

AES-HM76Z1FLi71	AES- HM76Z1FL with Intel Core i7 3517UE 1.7GHz
------------------------	--

AES-HM76Z1FLi31	AES- HM76Z1FL with Intel Core i3 3217UE 1.6GHz
------------------------	--

AES-HM76Z1FLCE1	AES- HM76Z1FL with Intel Celeron 1047UE 1.4GHz
------------------------	--

AES-HM76Z1FLCE2	AES- HM76Z1FL with Intel Celeron 927UE 1.5GHz
------------------------	---

