



GP Series

POS Terminal

The GP POS terminal with various platforms and its elegant appearance is highly recommended for hospitality market.



Easy storage
maintenance design



2nd LCD creates
interactive display



Splash-resistant on frontal



MSR / SCR and i-Button
Optional



Power Adaptor
Compartment



VESA for wall-mount



0°~85° Viewing angle

Specification

Model Name	GP-3460	GP-3462	GP-3472	GP-3474	GP-3476
Main board	IAT1-2550	IAT1-1037	IVP-76HM		
CPU	Intel Atom D2550 1.8 GHz Dual Core	Intel Celeron 1037U 1.8GHz Dual Core	Intel Core i3	Intel Core i5	Intel Core i7
Chipset	Intel NM10 Express	Intel NM70	Intel HM76 Express		
Main Memory	1GB DDRIII RAM				
Display Size	15" TFT-LCD with LED backlight				
Display Resolution	1024 x 768				
Touch Panel	5 wire resistive touch				
HDD	2.5" SATA HDD 320G				
Expansion	1 x Mini PCIe slot		1 x PCIe slot, 1xMini PCIe slot		
LAN	10 / 100M bps		10M / 100M / 1G bps		
OS Support	POSReady 2009, POSReady7, Windows XP / XPE, Windows 7, Windows 8(Ivy Bridge platform only), Linux				
Power	AC 100V~240V / 60W adapter		AC 100V~240V / 90W adapter		
External I/O Interface					
Serial Port	4 x External COM Port with 5V / 12V selectable				
Cash Drawer Port	1 x RJ11 with DC 12V (Standard / 24V)				
Keyboard Port	--	1 x PS / 2 (keyboard or Mouse)			
VGA Port	1 x VGA (DB15)				
Audio Jack	--	1 x Mic in, 1x Line out	1 x Line-in, 1x Line-out		
Speaker	2 x Integrated 1.5 W stereo speaker				
Ethernet Port	1 x RJ45 10M / 100 M / 1G Base-T				
USB Port	4 x USB 2.0 Type A	5 x USB 2.0 Type A	3 x USB 2.0 + 2 x USB 3.0 Type A		
DC Output	1 x 12V / 2.5A				
Optional Peripheral					
Magnetic Card Reader	ISO 7811 option 1 / 2 / 3 track				
Finger Print	512dpi x 8bit gray scale, Capture area: 14.6 x 18.1 mm				
i-button	Dallas Key				
Wireless LAN	802.11 b / g				
Customer Display	VFD / LCD Customer Display				
Second Display	8" / 11.6" / 15" TFT-LCD display				
Environment					
EMC & Safety	CE / FCC Class A				
Operating Temperature	5°C ~ 40°C				
Storage Temperature	-20°C ~ 60°C				
Operating Humidity	15%~80% RH				
Storage Humidity	20% ~90% RH				
Mechanical					
Housing Color	Black Cool White, Dark Gray				
Construction	ABS + SECC				
Dimension (W x D x H)	350 x 242 x 320 mm				
Weight (N.W.)	5.8 kg				

• Product specification is subject to change without prior notice.

POS Accessories



APPOSTAR

© 2014 APPOSTAR Technology Co., Ltd. All rights reserved.

13F., No.213, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)

Tel: 886-2-2910-6168 Fax: 886-2-2910-6199 Email: sales@appostar.com

