



SH-6650

SH-6650

Specification

All Modularized Design

15",17",19" TFT LCD Module (Support Multi-Sync)

8,16 PORT KVM switch Module (USB + PS/2)

8 Language Keyboard Module

Easy Change Modular. (Tooling loss Design.)

One person Quick and easy installation.

Sun Micro System supported.

Can Use for 520mm~980mm Cabinet Rack

*Heavy-duty steel electroplated for chassis

*Only 1U **4 IN 1** Drawer(LCD, KB, MOUSE,KVM Switch)

Keyboard Modules

*105 key Keyboard, compatible to IBM PC/AT, PS/2 keyboard, supports Windows function keys & [Sun Micro System Function Key](#) (Germany, English, French, Italian, Spanish, Japanese, Chinese, UK....optional)

*PS/2 Touchpad (Microsoft mouse compatible with PS/2 mouse interface)

Full Wheel Mouse emulation.Left, middle and right button emulation.

TFT LCD Modules

*19" TFT LCD Panel Module

*17" TFT LCD Panel Module

*15" TFT LCD Panel Module

-Built-in 7 languages OSD controls

-Backlight lifetime: 50,000 hrs.

-Sun Micro System Multi-Sync Supported.

-Sun Micro System 1152x900 Resolution Supported.

-Automatic flat panel shut-off when monitor is in the closed position, or no signal input.

KVM switch Modules (USB+PS2)

8/16 Port KVM switch

(108B/116B)

-Supported OS DOS,Win NT/9x/2000/2003/Me/XP,Linux,Unix,Novell,Free BSD,Solaris.

-Up to 8,16 Keyboard/VGA/Mouse inputs (8,16 PCs)

- Cascade control Max. up to 64/256 PCS
- Intelligent keyboard and mouse simulation, all PCs can booting in the same time.
- No software Required-Computer selection Via Pushbuttons, Hot keys, or OSD(On Screen Display)
- Quick View scan mode for monitoring selected computers
- Hot Pluggable-add or remove computer for maintenance without powering down the switch .
- Support Microsoft IntelliMouse (Pro), Optical Mouse, Logitech Mouse Man, Wheel Mouse, Scroll Point..
- Security lock function. (OSD)
- Auto Scan interval 1~255 sec.
- Supports VGA resolution up to 2048 x 1536 VESA DDC1/2B compatible
- Support DDC2B, correct Monitor type detection for each port
- Supports PS/2 interface by CB-K15P-xxx Cable.
- Supports USB & PS/2 interface for SUN Micro/Mac/PC by CB-K15UP-xxx Cable.

(108BS/116BS)

- Supports Two PS/2 Console.

Power Supply Modules

*Universal 100~240V AC input, 12V DC output power adapter Module
(UL/cUL/TUV/CE/FCC/CCC)

*SH-SDD30-48S12: 48V DC input adapter Optional

*SH-SDD30-24S12: 24V DC input adapter Optional

Cable

*CB-K15P-180: UL-2919 rated 3-in-1 cables set with VGA, keyboard (PS/2), Mouse (PS/2) 1.8M (3M, 5M, 10M, 20M, 30M Optional).

*CB-K15UP-180: UL-2919 rated 3-in-1 cables set with VGA, keyboard & Mouse (USB&PS/2) Used for SUN Micro/Mac/PC 1.8M (3M, 5M, 10M, 20M, 30M Optional).

Color

*Available in black. (Colors available for OEM)

Environmental Condition:

Operation Temp.: 0~50 degree C
Storage Temp.: -20~60 degree C
Humidity: 10~90%

Dimensions

W.482mm x **L.**610mm x **H.**44mm

N.W. 18 KGS

G.W. 22 KGS

CUFT. 2.95

Ordering Information:

Model	Computer port type	TFT Display	KVM switch	Cable
SH-6650-3-T-K-C-P	PS/2	15" TFT LCD Panel:	NO	CB-K15P-xxx
	USB+PS/2			CB-K15UP-xxx

SH-6650-4(108B) -T-K-C-P	PS/2	1024 x768 17" TFT LCD 19" TFT LCD Panel: 1280 x1024	8-port	CB-K15P-xxx
SH-6650-4(116B) -T-K-C-P	USB+PS/2		16-port	CB-K15UP-xxx
SH-6650-4(108BS) -T-K-C-P	PS/2 USB+PS/2	All Monitor Support Input signal: 1600 x 1200 1280 x 1024 1024 x 768 800 x 600 640 x 480 1152 x 900 for SUN Micro System	8-port Two PS/2 Console	CB-K15P-xxx CB-K15UP-xxx
SH-6650-4(116BS) -T-K-C-P			16-port Two PS/2 Console	

T=15:15" TFT LCD Monitor (Monitor Size)
17:17" TFT LCD Monitor
19:19" TFT LCD Monitor

K=Gr:Germany keyboard ,(Keyboard languages)
En:English keyboard,
Fr:French keyboard,
It:Italian keyboard,
Sp:Spanish keyboard,
Ja:Japanese keyboard,
Ch:Chinese keyboard,
UK: UK keyboard

C=B:Black Color(Color Code)

P=AC:Universal 100~240V AC Input 12V DC output Power Adapter
24:DC 24V Input 12V DC output Power Adapter
48:DC -48V Input 12V DC output Power Adapter

xxx=180:180cm cable
300:300cm cable
500:500cm cable
1000:10m cable
2000:20m cable
3000:30m cable

The specifiction and pictures are subject to change without notice.

All trademarks and logos are the properties of their respective holders.